




Cove 2 Opal



Housing

Matt natural anodized, aluminum extrusion profile and stainless steel mounting accessories with plastic end cap.

Optics

Opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L70B50 \geq 50,000 hours of lifetime.

Driver

24Vdc external type. Constant voltage output driver with high efficiency.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	L (mm)
SDCVK.135.3.30	3	3000	240	>80	24V DC	0,06	135
SDCVK.135.3.40	3	4000	260	>80	24V DC	0,06	135
SDCVK.260.6.30	6	3000	490	>80	24V DC	0,10	260
SDCVK.260.6.40	6	4000	520	>80	24V DC	0,10	260
SDCVK.505.12.30	12	3000	990	>80	24V DC	0,19	505
SDCVK.505.12.40	12	4000	1070	>80	24V DC	0,19	505
SDCVK.1000.24.30	24	3000	2040	>80	24V DC	0,37	1000
SDCVK.1000.24.40	24	4000	2170	>80	24V DC	0,37	1000
SDCVK.1245.30.30	30	3000	2480	>80	24V DC	0,46	1245
SDCVK.1245.30.40	30	4000	2640	>80	24V DC	0,46	1245
SDCVK.1495.36.30	36	3000	2980	>80	24V DC	0,55	1495
SDCVK.1495.36.40	36	4000	3170	>80	24V DC	0,55	1495

