E 3012 HYL



Hylum has a high quality LED with 90 CRI white color. The fixture is ideal for hygienic environments and can be easily cleaned. It can be easily installed with practical mounting parts and mounting method. As a product with IP protection; Since there are no bolts etc. connection parts on the visible surface, it does not disrupt the visual aesthetics and does not compromise on simplicity and elegance.

Housing
Antibacterial electrostatic powder coated DKP sheet metal body and aluminum frame

Diffuser
UV resistant, non-yellowing, opal white polystyrene diffuser providing homogeneous light distribution

Glass
Transparent, tempered glass

LedMid power led with high efficacy factor and high color rendering
Achieving L80B50 ≥ 50.000 hours of lifetime


Driver
Constant current output LED driver with high efficiency, Pf ≥ 0.90

Ambient Temperature
-25 °C/+35 °C (With emergency lighting unit +5 °C/ +30 °C)

Options3 hours emergency lighting kit
Dimming via DALI (Green-White model is dimming via DALI as standard)

Ral 9016

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Cut-out Size (mm)
EHYL. 3012.25.30.90	25	3000	2100	>90	220 - 240 / 50 - 60	12	280x1180
EHYL. 3012.25.40.90	25	4000	2300	>90	220 - 240 / 50 - 60	12	280x1180
EHYL. 3012.32.30.90	32	3000	2700	>90	220 - 240 / 50 - 60	12	280x1180
EHYL. 3012.32.40.90	32	4000	2900	>90	220 - 240 / 50 - 60	12	280x1180
EHYL. 3012.59.30.90	59	3000	4700	>90	220 - 240 / 50 - 60	12	280x1180
EHYL. 3012.59.40.90	59	4000	5000	>90	220 - 240 / 50 - 60	12	280x1180


1195
1111
295
211
121
Min. 10
Max. 60