
Diamond




Housing
Matte natural anodized, aluminum extrusion profile and stainless steel mounting accessories with plastic end cap.

Optics
Acrylic transparent optical lens.
Led
High-efficacy mid power LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime.
Driver
24Vdc external type. Constant voltage output driver with high efficiency.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle	L (mm)
SDDMD.300.15.30.55	15	3000	1080	>80	24V DC	0,30	9°/55°	300
SDDMD.300.15.40.55	15	4000	1160	>80	24V DC	0,30	9°/55°	300
SDDMD.600.30.30.55	30	3000	2160	>80	24V DC	0,60	9°/55°	600
SDDMD.600.30.40.55	30	4000	2320	>80	24V DC	0,60	9°/55°	600
SDDMD.900.45.30.55	45	3000	3240	>80	24V DC	0,90	9°/55°	900
SDDMD.900.45.40.55	45	4000	3480	>80	24V DC	0,90	9°/55°	900
SDDMD.1200.60.30.55	60	3000	4320	>80	24V DC	1,2	9°/55°	1200
SDDMD.1200.60.40.55	60	4000	4640	>80	24V DC	1,2	9°/55°	1200
SDDMD.1500.75.30.55	75	3000	5660	>80	24V DC	1,5	9°/55°	1500
SDDMD.1500.75.40.55	75	4000	6090	>80	24V DC	1,5	9°/55°	1500


105°
105°
90°
90°
75°
75°
60°
60°
45°
45°
2000
3000
5000
30°
15°
0°
15°
30°
cd/klm
η = 100%
C0 - C180
C90 - C270


42
60
L
60