



# DS 1023 MON



## Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

## Optics

Opal white polystyrene diffuser with lambertian light distribution.

## Led

High-efficacy Mid power LED module with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and  $Pf \geq 0.95$

**Operating Temperature Range** 0 °C/+35 °C

## Options

Dimming via DALI



Ral 9016 Ral 9005 Ral 9006

| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|
| DSMON.260.21.30 | 21        | 3000    | 1940              | >80 | 220 - 240 / 50 - 60 | 1,5         |
| DSMON.260.21.40 | 21        | 4000    | 2090              | >80 | 220 - 240 / 50 - 60 | 1,5         |
| DSMON.260.30.30 | 30        | 3000    | 2680              | >80 | 220 - 240 / 50 - 60 | 1,5         |
| DSMON.260.30.40 | 30        | 4000    | 2900              | >80 | 220 - 240 / 50 - 60 | 1,5         |



