



# DS 1020 MON



## Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

## Optics

Opal white polystyrene diffuser with lambertian light distribution.

## Led

High-efficacy Mid power LED module with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and  $Pf \geq 0.95$

**Operating Temperature Range** 0 °C/+35 °C

## Options

Dimming via DALI



Ral 9016 Ral 9005 Ral 9006

| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|
| DSMON.230.14.30 | 14        | 3000    | 1240              | >80 | 220 - 240 / 50 - 60 | 1,3         |
| DSMON.230.14.40 | 14        | 4000    | 1330              | >80 | 220 - 240 / 50 - 60 | 1,3         |
| DSMON.230.20.30 | 20        | 3000    | 1610              | >80 | 220 - 240 / 50 - 60 | 1,3         |
| DSMON.230.20.40 | 20        | 4000    | 1730              | >80 | 220 - 240 / 50 - 60 | 1,3         |



