



DS 1016 MON



Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

Optics

Opal white polystyrene diffuser with lambertian light distribution.

Led

High-efficacy Mid power LED module with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Operating Temperature Range 0 °C/+35 °C

Options

Dimming via DALI



Ral 9016 Ral 9005 Ral 9006

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|
| DSMON.187.9.40 | 9 | 4000 | 795 | >80 | 220 - 240 / 50 - 60 | 0,9 |
| DSMON.187.9.30 | 9 | 3000 | 740 | >80 | 220 - 240 / 50 - 60 | 0,9 |
| DSMON.187.13.30 | 13 | 3000 | 975 | >80 | 220 - 240 / 50 - 60 | 0,9 |
| DSMON.187.13.40 | 13 | 4000 | 1050 | >80 | 220 - 240 / 50 - 60 | 0,9 |



