G 3012 EPM (1)



Housing
Aluminium profile frame, steel back cover with electrostatic
powder coating

Optics
PS microprism louvre, PMMA LGP diffuser (UGR<19)


Led
High-efficiency LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.


Driver
Constant current output LED driver with high efficiency,
Pf ≥ 0.95

Installation
For T-bar ceiling only (15 or 24 mm)

Ral 9016

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)
GEPM+.3012.19.40	19	4000	2410	>80	220 - 240 / 50 - 60	3,42
GEPM+.3012.19.30	19	3000	2150	>80	220 - 240 / 50 - 60	3,48
GEPM+.3012.27.40	27	4000	3350	>80	220 - 240 / 50 - 60	3,48
GEPM+.3012.27.30	27	3000	3000	>80	220 - 240 / 50 - 60	3,48
GEPM+.3012.30.40	30	4000	3680	>80	220 - 240 / 50 - 60	3,48
GEPM+.3012.30.30	30	3000	3410	>80	220 - 240 / 50 - 60	3,48


105°
105°
90°
90°
75°
75°
60°
60°
45°
45°
200
300
400
500
30°
15°
0°
15°
30°
cd/klm
C0 - C180
C90 - C270


1195
1147
295
247
40
10