



# G 3012 EPO (1)



## Housing

Aluminium profile frame, steel back cover with electrostatic powder coating

## Optics

PS opal diffuser, PMMA LGP diffuser

## Led

High-efficiency LED with CRI>80, achieving L90B50  $\geq$  50,000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency, Pf  $\geq$  0.95

## Installation

For T-bar ceiling only (15 or 24 mm)



Ral 9016

| Type Code        | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|------------------|-----------|---------|-------------------|-----|---------------------|-------------|
| GEPO+.3012.19.40 | 19        | 4000    | 2590              | >80 | 220 - 240 / 50 - 60 | 3,48        |
| GEPO+.3012.19.30 | 19        | 3000    | 2470              | >80 | 220 - 240 / 50 - 60 | 3,48        |
| GEPO+.3012.27.40 | 27        | 4000    | 3550              | >80 | 220 - 240 / 50 - 60 | 3,48        |
| GEPO+.3012.27.30 | 27        | 3000    | 3400              | >80 | 220 - 240 / 50 - 60 | 3,48        |
| GEPO+.3012.30.40 | 30        | 4000    | 3970              | >80 | 220 - 240 / 50 - 60 | 3,48        |
| GEPO+.3012.30.30 | 30        | 3000    | 3850              | >80 | 220 - 240 / 50 - 60 | 3,48        |

