



Phantom Optic Lens



Housing

Electrostatic powder painted ,aluminum extrusion profile

Optics

Optic acrylic lens

Reflector

Matt anodized aluminium

Louver

Anti-glare electrostatic powder painted sheet

Led

High-efficacy mid power LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and P_f≥0.95



Ral 9016 Ral 9005 Ral 9006

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle	L (mm)	L1 (mm)
SRPAN. 880.42.30.55/85	42	3000	4510	>80	220 - 240 / 50 - 60	3	55°/85°	880	990
SRPAN. 880.42.40.55/85	42	4000	4800	>80	220 - 240 / 50 - 60	3	55°/85°	880	990
SRPAN. 1450.68.30.55/85	68	3000	7750	>80	220 - 240 / 50 - 60	4,90	55°/85°	1450	1567
SRPAN. 1450.68.40.55/85	68	4000	8240	>80	220 - 240 / 50 - 60	4,90	55°/85°	1450	1567
SRPAN. 600.29.30.55/85	29	3000	3060	>80	220 - 240 / 50 - 60	2,50	55°/85°	602	710
SR.PAN. 600.29.40.55/85	29	4000	3250	>80	220 - 240 / 50 - 60	2,50	55°/85°	602	710
SRDAN. 1450.72.30.55/85	63	3000	6000	>80	220 - 240 / 50 - 60	4,90			
SRDAN. 1450.72.40.55/85	63	4000	6440	>80	220 - 240 / 50 - 60	4,90			
SRDAN. 1450.72.30.55/85 (1)	144	3000	13800	>80	220 - 240 / 50 - 60	4,90			
SRDAN. 1450.72.30.55/85 (2)	144	4000	14800	>80	220 - 240 / 50 - 60	4,90			

