



DS 1011 PLA



Installation Installation on three-phase track.

Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

Optics

97% reflective, matte, anodized 1090 aluminum alloy reflector with 99.99% pure silver reflection layer and A+ efficiency rate according to EN 16268 standard.

Led

High-efficiency COB LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and P_f≥0.95

Ambient Temperature 0 °C / +25 °C

Options

- * Clear tempered glass
- * Dimming via DALI



Ral 9016 Ral 9005

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
DSPLA. 11.19.30.24.80	19	3000	2330	>80	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.19.40.24.80	19	4000	2480	>80	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.27.30.24.80	27	3000	3070	>80	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.27.40.24.80	27	4000	3240	>80	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.35.30.24.80	35	3000	3540	>80	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.35.40.24.80	35	4000	3800	>80	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.19.30.24.90	19	3000	2070	>90	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.19.40.24.90	19	4000	2170	>90	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.27.30.24.90	27	3000	2650	>90	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.27.40.24.90	27	4000	3000	>90	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.35.30.24.90	35	3000	3340	>90	220 - 240 / 50 - 60	1,25	24°
DSPLA. 11.35.40.24.90	35	4000	3490	>90	220 - 240 / 50 - 60	1,25	24°

