



DG 1012 MGW



Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink

Difuser Tempered glass with frosted

LED High-efficacy mid power LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime

Driver Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range 0 °C/+35 °C

Option DALI and Emergency Lighting Kit



Ral 9016 Ral 9005 Ral 9006

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| DGMGW.120.7.40 | 7 | 4000 | 670 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |
| DGMGW.120.7.30 | 7 | 3000 | 620 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |
| DGMGW.120.10.40 | 10 | 4000 | 950 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |
| DGMGW.120.10.30 | 10 | 3000 | 870 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |



