# DG 1012 MON



**Housing**
Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink

**Difuser**Opal white diffuser with lambertian light distribution and high transmissivity

**LED**High-efficacy mid power LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime


**Driver**Constant current output LED driver with high efficiency and Pf≥0.90


**Operating Temperature Range**0 °C/+35 °C

**Option**DALI and Emergency Lighting Kit

Ral 9016 Ral 9005 Ral 9006

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Cut-out Size (mm) |
|---|---|---|---|---|---|---|---|
| DGMON.120.7.40 | 7 | 4000 | 650 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |
| DGMON.120.7.30 | 7 | 3000 | 590 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |
| DGMON.120.10.40 | 10 | 4000 | 910 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |
| DGMON.120.10.30 | 10 | 3000 | 830 | >80 | 220 - 240 / 50 - 60 | 0,5 | Ø105 |




IP20
IP54
77
∅120