



# DG 1012 MON



## Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink

**Diffuser** Opal white diffuser with lambertian light distribution and high transmissivity

**LED** High-efficacy mid power LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime

**Driver** Constant current output LED driver with high efficiency and P<sub>f</sub>≥0.90

**Operating Temperature Range** 0 °C/+35 °C

**Option** DALI and Emergency Lighting Kit



Ral 9016 Ral 9005 Ral 9006

| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| DGMON.120.7.40  | 7         | 4000    | 650               | >80 | 220 - 240 / 50 - 60 | 0,5         | Ø105              |
| DGMON.120.7.30  | 7         | 3000    | 590               | >80 | 220 - 240 / 50 - 60 | 0,5         | Ø105              |
| DGMON.120.10.40 | 10        | 4000    | 910               | >80 | 220 - 240 / 50 - 60 | 0,5         | Ø105              |
| DGMON.120.10.30 | 10        | 3000    | 830               | >80 | 220 - 240 / 50 - 60 | 0,5         | Ø105              |



