



DG 1016 MON+



Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

Optics Opal white polystyrene diffuser with lambertian light distribution and.

Led High-efficacy LED module with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

Driver Constant current output LED driver with high efficiency and pf >0,9.

Operating Temperature Range 0 °C/+35 °C

Options

- * 1 or 3 hours emergency lighting kit
- * Dimming via DALI



Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Cut-out Size (mm)
DGMON+.160.8.30	8	3000	950	>80	220 - 240 / 50 - 60	0,6	Ø142
DGMON+.160.8.40	8	4000	1030	>80	220 - 240 / 50 - 60	0,6	Ø142
DGMON+.160.11.30	11	3000	1320	>80	220 - 240 / 50 - 60	0,6	Ø142
DGMON+.160.11.40	11	4000	1410	>80	220 - 240 / 50 - 60	0,6	Ø142
DGMON+.160.15.30	15	3000	1700	>80	220 - 240 / 50 - 60	0,6	Ø142
DGMON+.160.15.40	15	4000	1840	>80	220 - 240 / 50 - 60	0,6	Ø142



