



G 6060 DRO



Housing

Sheet steel body with electrostatic powder coating.

Optics

Opal white diffuser with high transmissivity.

Led

High-efficacy LED MODULE with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and Pf≥0.95

Options

1 or 3 hours emergency lighting kit
Dimming via DALI



| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| GDRO.6060.36.30 | 36 | 3000 | 3740 | >80 | 220 - 240 / 50 - 60 | 4,7 | 580x580 |
| GDRO.6060.36.40 | 36 | 4000 | 4100 | >80 | 220 - 240 / 50 - 60 | 4,7 | 580x580 |
| GDRO.6060.28.30 | 28 | 3000 | 2730 | >80 | 220 - 240 / 50 - 60 | 4,7 | 580x580 |
| GDRO.6060.28.40 | 28 | 4000 | 3000 | >80 | 220 - 240 / 50 - 60 | 4,7 | 580x580 |

