
G 6060 BOX



Housing
Sheet steel body with electrostatic powder coating.

Optics
Opal white polystyrene diffuser with lambertian light distribution.


LedHigh-efficacy LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.


Driver
Constant current output LED driver with high efficiency and Pf≥0.95


Options
* 1 or 3 hours emergency lighting kit
* Dimming via DALI

Ral 9016 Ral 9006

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Cut-out Size (mm)
GBOX.6060.36.30	36	3000	3220	>80	220 - 240 / 50 - 60	4,7	580x580
GBOX.6060.36.40	36	4000	3540	>80	220 - 240 / 50 - 60	4,7	580x580
GBOX.6060.28.30	28	3000	2340	>80	220 - 240 / 50 - 60	4,7	580x580
GBOX.6060.28.40	28	4000	2580	>80	220 - 240 / 50 - 60	4,7	580x580




573
573
75
595
595


3X bondmix
4X bondmix
4X bondy
4X bondmix
A
12X A+B+Cmix
A
4X bondmix
B
B
4X bondt
4X bondmix
4X bondmix
C
6X bondmix
16X bondmix
9X bondmix
6X B+Cmix
B
C