



# G 6060 SQU



## Housing

Sheet steel body with electrostatic powder coating.

## Optics

Opal white polystyrene diffuser with lambertian light distribution.


**LED** High-efficiency LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and Pf≥0.95

## Options

- \* 1 or 3 hours emergency lighting kit
- \* Dimming via DALI



| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| GSQU.6060.36.30 | 36        | 3000    | 2650              | >80 | 220 - 240 / 50 - 60 | 4,9         | 580x580           |
| GSQU.6060.36.40 | 36        | 4000    | 2990              | >80 | 220 - 240 / 50 - 60 | 4,9         | 580x580           |
| GSQU.6060.28.30 | 28        | 3000    | 1960              | >80 | 220 - 240 / 50 - 60 | 4,9         | 580x580           |
| GSQU.6060.28.40 | 28        | 4000    | 2110              | >80 | 220 - 240 / 50 - 60 | 4,9         | 580x580           |

