



G 6060 SQU



Housing

Sheet steel body with electrostatic powder coating.

Optics

Opal white polystyrene diffuser with lambertian light distribution.


Led High-efficiency LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and Pf≥0.95

Options

- * 1 or 3 hours emergency lighting kit
- * Dimming via DALI



| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| GSQU.6060.36.30 | 36 | 3000 | 2650 | >80 | 220 - 240 / 50 - 60 | 4,9 | 580x580 |
| GSQU.6060.36.40 | 36 | 4000 | 2990 | >80 | 220 - 240 / 50 - 60 | 4,9 | 580x580 |
| GSQU.6060.28.30 | 28 | 3000 | 1960 | >80 | 220 - 240 / 50 - 60 | 4,9 | 580x580 |
| GSQU.6060.28.40 | 28 | 4000 | 2110 | >80 | 220 - 240 / 50 - 60 | 4,9 | 580x580 |

