



DG 2015 KRA



Housing

Aluminum injection frame with electrostatic powder coating and die-cast aluminum heatsink.

Optics

Highly efficient PMMA lens, designed specially for High Power LED.

Led

High-efficacy High Power LED with CRI>80, achieving L70B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and pf >0,9.

Options

- * Dimming via DALI
- * 80° and 50° light distribution for lens
- * Black and White color option for reflector

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle	Color
DGKRA. 150.10.30.80	10	3000	915	>80	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)
DGKRA. 150.10.30.90	10	3000	881	>90	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)
DGKRA. 150.10.40.80	10	4000	971	>80	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)
DGKRA. 150.10.40.90	10	4000	934	>90	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)
DGKRA. 150.17.30.80	17	3000	1405	>80	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)
DGKRA. 150.17.30.90	17	3000	1340	>90	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)
DGKRA. 150.17.40.80	17	4000	1540	>80	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)
DGKRA. 150.17.40.90	17	4000	1485	>90	220 - 240 / 50 - 60	0,36	40	Beyaz Kasa (White Body)

