



G 6060 EPB



Housing

Sheet steel body with electrostatic powder coating.

Optics

Prismatic structured opal white diffuser with lambertian light distribution and high transmissivity.

LED High-efficiency LED with CRI>80, achieving L90B50 \geq 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Options

1 or 3 hours emergency lighting kit
Dimming via DALI



Ral 9016

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| GEPB.6060.44.30 | 44 | 3000 | 3620 | >80 | 220 - 240 / 50 - 60 | 4,6 | 580x580 |
| GEPB.6060.44.40 | 44 | 4000 | 3880 | >80 | 220 - 240 / 50 - 60 | 4,6 | 580x580 |
| GEPB.6060.27.30 | 27 | 3000 | 2570 | >80 | 220 - 240 / 50 - 60 | 4,6 | 580x580 |
| GEPB.6060.27.40 | 27 | 4000 | 2700 | >80 | 220 - 240 / 50 - 60 | 4,6 | 580x580 |

