



G 6060 PLK



Housing

Sheet steel body with electrostatic powder coating.

Optics

Opal white polystyrene diffuser with lambertian light distribution.

Led

High-efficiency LED with CRI>80, achieving L90B50 \geq 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Options

1 or 3 hours emergency lighting kit
Dimming via DALI



Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)
GPLK.6060.20.30	20	3000	2370	>80	220 - 240 / 50 - 60	3,1
GPLK.6060.20.40	20	4000	2530	>80	220 - 240 / 50 - 60	3,1
GPLK.6060.27.30	27	3000	3080	>80	220 - 240 / 50 - 60	3,1
GPLK.6060.27.40	27	4000	3280	>80	220 - 240 / 50 - 60	3,1
GPLK.6060.36.30	36	3000	3970	>80	220 - 240 / 50 - 60	3,1
GPLK.6060.36.40	36	4000	4230	>80	220 - 240 / 50 - 60	3,1
GPLK.6060.42.30	42	3000	4460	>80	220 - 240 / 50 - 60	3,1
GPLK.6060.42.40	42	4000	4750	>80	220 - 240 / 50 - 60	3,1



