



G 6060 PLK



Housing

Sheet steel body with electrostatic powder coating.

Optics

Opal white polystyrene diffuser with lambertian light distribution.

Led

High-efficiency LED with CRI>80, achieving L90B50 $\geq 50,000$ hours of lifetime.

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Options

1 or 3 hours emergency lighting kit
Dimming via DALI



Ral 9016 Ral 9006

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|
| GPLK.6060.20.30 | 20 | 3000 | 2370 | >80 | 220 - 240 / 50 - 60 | 3,1 |
| GPLK.6060.20.40 | 20 | 4000 | 2530 | >80 | 220 - 240 / 50 - 60 | 3,1 |
| GPLK.6060.27.30 | 27 | 3000 | 3080 | >80 | 220 - 240 / 50 - 60 | 3,1 |
| GPLK.6060.27.40 | 27 | 4000 | 3280 | >80 | 220 - 240 / 50 - 60 | 3,1 |
| GPLK.6060.36.30 | 36 | 3000 | 3970 | >80 | 220 - 240 / 50 - 60 | 3,1 |
| GPLK.6060.36.40 | 36 | 4000 | 4230 | >80 | 220 - 240 / 50 - 60 | 3,1 |
| GPLK.6060.42.30 | 42 | 3000 | 4460 | >80 | 220 - 240 / 50 - 60 | 3,1 |
| GPLK.6060.42.40 | 42 | 4000 | 4750 | >80 | 220 - 240 / 50 - 60 | 3,1 |



