



G 6060 PPL



Housing

Sheet steel body with electrostatic powder coating.

Optics

Opal white polystyrene diffuser with lambertian light distribution.

Led

High-efficiency LED with CRI>80, achieving L90B50 \geq 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Options

1 or 3 hours emergency lighting kit
Dimming via DALI



| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| GPPL.6060.20.30 | 20 | 3000 | 2200 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |
| GPPL.6060.20.40 | 20 | 4000 | 2360 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |
| GPPL.6060.27.30 | 27 | 3000 | 2900 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |
| GPPL.6060.27.40 | 27 | 4000 | 3080 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |
| GPPL.6060.36.30 | 36 | 3000 | 3750 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |
| GPPL.6060.36.40 | 36 | 4000 | 3980 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |
| GPPL.6060.42.30 | 42 | 3000 | 4160 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |
| GPPL.6060.42.40 | 42 | 4000 | 4430 | >80 | 220 - 240 / 50 - 60 | 3,7 | 580x580 |

