



# G 6060 PPT



## Housing

Sheet steel body with electrostatic powder coating.

## Optics

Opal white polystyrene diffuser with lambertian light distribution.

## Led

High-efficiency LED with CRI>80, achieving L90B50  $\geq 50,000$  hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and  $Pf \geq 0.95$

## Options

- \* 1 or 3 hours emergency lighting kit
- \* Dimming via DALI



| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|
| GPPT.6060.20.30 | 20        | 3000    | 2390              | >80 | 220 - 240 / 50 - 60 | 3,2         |
| GPPT.6060.20.40 | 20        | 4000    | 2540              | >80 | 220 - 240 / 50 - 60 | 3,2         |
| GPPT.6060.27.30 | 27        | 3000    | 3110              | >80 | 220 - 240 / 50 - 60 | 3,2         |
| GPPT.6060.27.40 | 27        | 4000    | 3300              | >80 | 220 - 240 / 50 - 60 | 3,2         |
| GPPT.6060.36.30 | 36        | 3000    | 4000              | >80 | 220 - 240 / 50 - 60 | 3,2         |
| GPPT.6060.36.40 | 36        | 4000    | 4250              | >80 | 220 - 240 / 50 - 60 | 3,2         |
| GPPT.6060.42.30 | 42        | 3000    | 4490              | >80 | 220 - 240 / 50 - 60 | 3,2         |
| GPPT.6060.42.40 | 42        | 4000    | 4780              | >80 | 220 - 240 / 50 - 60 | 3,2         |



