



G 6060 MPL



Gövde

Elektrostatik toz boyalı DKP sac

Difüzör

PMMA Mikroprizmatik lens + 0,5mm opal PC difüzör

Led

L70B50 ye göre ≥ 50.000 saat, yüksek etkinlik faktörüne ve renksel geriverime sahip mid power

Sürücü Sabit akım çıkışlı, yüksek geri verimli, Pf ≥ 0.95 .

UGR (Kamaşma)

36W : (4H-8H 70/50/20) <19,2

28W : (4H-8H 70/50/20) <19

Opsiyon

* 1 veya 3 saat süreli acil aydınlatma modülü

* Dalı dim edilebilir



Tip Kodu	Güç (w)	CCT (K)	Işık Akısı (lm)	CRI	V/Hz	Ağırlık (Kg)	Montaj Ölçüsü (mm)
GMPL.6060.36.30	36	3000	3280	>80	220 - 240 / 50 - 60	4	580x580
GMPL.6060.36.40	36	4000	3545	>80	220 - 240 / 50 - 60	4	580x580
GMPL.6060.28.30	28	3000	2550	>80	220 - 240 / 50 - 60	4	580x580
GMPL.6060.28.40	28	4000	2750	>80	220 - 240 / 50 - 60	4	580x580

