G 6060 EPO



Housing
Aluminium profile frame, steel back cover with electrostatic
powder coating

Optics
PS opal diffuser, PMMA LGP diffuser


Led
High-efficiency LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.


Driver
Constant current output LED driver with high efficiency,
Pf ≥ 0.95

Installation
For T-bar ceiling only (15 or 24 mm)

Ral 9016

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)
GEPO.6060.20.40	20	4000	2350	>80	220 - 240 / 50 - 60	3,33
GEPO.6060.20.30	20	3000	2210	>80	220 - 240 / 50 - 60	3,33
GEPO.6060.27.40	27	4000	3160	>80	220 - 240 / 50 - 60	3,33
GEPO6060.27.30	27	3000	2970	>80	220 - 240 / 50 - 60	3,33
GEPO.6060.36.40	36	4000	3800	>80	220 - 240 / 50 - 60	3,33
GEPO.6060.36.30	36	3000	3440	>80	220 - 240 / 50 - 60	3,33
GEPOP.6060.19.40	19	4000	2430	>80	220 - 240 / 50 - 60	3,33
GEPOP.6060.19.30	19	3000	2290	>80	220 - 240 / 50 - 60	3,33
GEPOP.6060.27.40	27	4000	3380	>80	220 - 240 / 50 - 60	3,33
GEPOP.6060.27.30	27	3000	3180	>80	220 - 240 / 50 - 60	3,33
GEPOP.6060.30.40	30	4000	4100	>80	220 - 240 / 50 - 60	3,33
GEPOP.6060.30.30	30	3000	3910	>80	220 - 240 / 50 - 60	3,33


105°
105°
90°
90°
75°
75°
60°
60°
160
45°
240
45°
320
30°
15°
0°
15°
30°
cd/klm
C0 - C180
C90 - C270


595
547
595
547
40
10