



G 6060 RAL



Housing

Sheet steel body with electrostatic powder coating.

Optics

Anti-glare reflector and 80° optical lens

Led High-efficiency LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and P_f≥0.95

Options

1 or 3 hours emergency lighting kit

Dimming via DALI

Black and white color option for reflector



Ral 9016 Double

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) |
|-----------------------|-----------|---------|-------------------|-----|---------------------|-------------|
| GRAL.6060.B. 23.30 | 23 | 3000 | 2920 | >80 | 220 - 240 / 50 - 60 | 5,4 |
| GRAL.6060.B. 23.40 | 23 | 4000 | 3110 | >80 | 220 - 240 / 50 - 60 | 5,4 |
| GRAL.6060.B. 30.30 | 30 | 3000 | 3950 | >80 | 220 - 240 / 50 - 60 | 5,4 |
| GRAL.6060.B. 30.40 | 30 | 4000 | 4200 | >80 | 220 - 240 / 50 - 60 | 5,4 |
| GRAL.6060.W. 23.30 | 23 | 3000 | 3260 | >80 | 220 - 240 / 50 - 60 | 5,4 |
| GRAL.6060.W. 23.40 | 23 | 4000 | 3460 | >80 | 220 - 240 / 50 - 60 | 5,4 |
| GRAL.6060.W. 30.30 | 30 | 3000 | 4410 | >80 | 220 - 240 / 50 - 60 | 5,4 |
| GRAL.6060.W. 30.40 | 30 | 4000 | 4700 | >80 | 220 - 240 / 50 - 60 | 5,4 |

