



# G 6060 RAL



## Housing

Sheet steel body with electrostatic powder coating.

## Optics

Anti-glare reflector and 80° optical lens

**Led** High-efficiency LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and P<sub>f</sub>≥0.95

## Options

1 or 3 hours emergency lighting kit

Dimming via DALI

Black and white color option for reflector



Ral 9016 Double

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)
GRAL.6060.B. 23.30	23	3000	2920	>80	220 - 240 / 50 - 60	5,4
GRAL.6060.B. 23.40	23	4000	3110	>80	220 - 240 / 50 - 60	5,4
GRAL.6060.B. 30.30	30	3000	3950	>80	220 - 240 / 50 - 60	5,4
GRAL.6060.B. 30.40	30	4000	4200	>80	220 - 240 / 50 - 60	5,4
GRAL.6060.W. 23.30	23	3000	3260	>80	220 - 240 / 50 - 60	5,4
GRAL.6060.W. 23.40	23	4000	3460	>80	220 - 240 / 50 - 60	5,4
GRAL.6060.W. 30.30	30	3000	4410	>80	220 - 240 / 50 - 60	5,4
GRAL.6060.W. 30.40	30	4000	4700	>80	220 - 240 / 50 - 60	5,4

