



# SD 6060 PPL



### Housing

Sheet steel body with electrostatic powder coating.

### Optics

Opal white polystyrene diffuser with lambertian light distribution.

### Led


High-efficiency LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

### Driver

Constant current output LED driver with high efficiency and  $Pf \geq 0.95$

### Options

- \* 1 or 3 hours emergency lighting kit
- \* Dimming via DALI



Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)
SDPPL.6060.20.30	20	3000	1950	>80	220 - 240 / 50 - 60	4,0
SDPPL.6060.20.40	20	4000	2080	>80	220 - 240 / 50 - 60	4,0
SDPPL.6060.27.30	27	3000	2520	>80	220 - 240 / 50 - 60	4,0
SDPPL.6060.27.40	27	4000	2680	>80	220 - 240 / 50 - 60	4,0
SDPPL.6060.36.30	36	3000	3270	>80	220 - 240 / 50 - 60	4,0
SDPPL.6060.36.40	36	4000	3480	>80	220 - 240 / 50 - 60	4,0
SDPPL.6060.42.30	42	3000	3710	>80	220 - 240 / 50 - 60	4,0
SDPPL.6060.42.40	42	4000	3950	>80	220 - 240 / 50 - 60	4,0

