



SD 6060 PPL



Housing

Sheet steel body with electrostatic powder coating.

Optics

Opal white polystyrene diffuser with lambertian light distribution.

Led

High-efficiency LED with CRI>80, achieving L90B50 $\geq 50,000$ hours of lifetime.

Driver

Constant current output LED driver with high efficiency and $Pf \geq 0.95$

Options

- * 1 or 3 hours emergency lighting kit
- * Dimming via DALI



| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) |
|------------------|-----------|---------|-------------------|-----|---------------------|-------------|
| SDPPL.6060.20.30 | 20 | 3000 | 1950 | >80 | 220 - 240 / 50 - 60 | 4,0 |
| SDPPL.6060.20.40 | 20 | 4000 | 2080 | >80 | 220 - 240 / 50 - 60 | 4,0 |
| SDPPL.6060.27.30 | 27 | 3000 | 2520 | >80 | 220 - 240 / 50 - 60 | 4,0 |
| SDPPL.6060.27.40 | 27 | 4000 | 2680 | >80 | 220 - 240 / 50 - 60 | 4,0 |
| SDPPL.6060.36.30 | 36 | 3000 | 3270 | >80 | 220 - 240 / 50 - 60 | 4,0 |
| SDPPL.6060.36.40 | 36 | 4000 | 3480 | >80 | 220 - 240 / 50 - 60 | 4,0 |
| SDPPL.6060.42.30 | 42 | 3000 | 3710 | >80 | 220 - 240 / 50 - 60 | 4,0 |
| SDPPL.6060.42.40 | 42 | 4000 | 3950 | >80 | 220 - 240 / 50 - 60 | 4,0 |



