



S 0415 FLS



Housing

Electrostatic powder coated aluminium injection and air pressure balancer (ventile) silicon gasket.

Optics

Special design clear polycarbonate optic lens to transparent glass microprism deglaring lens option.

Led

L85B50>50000 hours rated useful lifetime, high efficacy and color rendering index pf>0,95.

Driver

Highly efficient with constant current output.

Ambient Temperature

180W : -20 °C/+35 °C
 150W : -20 °C/+40 °C
 105W : -20 °C/+45 °C
 70W : -20 °C/+60 °C

Options Dimming via DALI

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Beam Angle |
|---------------------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SFLS. 415.180.M1.40.66 | 180 | 4000 | 23580 | >80 | 220 - 240 / 50 - 60 | 6,7 | 66° |
| SFLS. 415.180.M2.40.66 | 180 | 4000 | 23580 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.180.M3.40.66 | 180 | 4000 | 23580 | >80 | 220 - 240 / 50 - 60 | 6,9 | 66° |
| SFLS. 415.180.M4.40.66 | 180 | 4000 | 23580 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.180.M5.40.66 | 180 | 4000 | 23580 | >80 | 220 - 240 / 50 - 60 | 7,0 | 66° |
| SFLS. 415.150.M1.40.66 | 150 | 4000 | 20400 | >80 | 220 - 240 / 50 - 60 | 6,7 | 66° |
| SFLS. 415.150.M2.40.66 | 150 | 4000 | 20400 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.150.M3.40.66 | 150 | 4000 | 20400 | >80 | 220 - 240 / 50 - 60 | 6,9 | 66° |
| SFLS. 415.150.M4.40.66 | 150 | 4000 | 20400 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.150.M5.40.66 | 150 | 4000 | 20400 | >80 | 220 - 240 / 50 - 60 | 7,0 | 66° |
| SFLS. 415.105.M1.40.66 | 105 | 4000 | 15020 | >80 | 220 - 240 / 50 - 60 | 6,7 | 66° |
| SFLS. 415.105.M2.40.66 | 105 | 4000 | 15020 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.105.M3.40.66 | 105 | 4000 | 15020 | >80 | 220 - 240 / 50 - 60 | 6,9 | 66° |
| SFLS. 415.105.M4.40.66 | 105 | 4000 | 15020 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.105.M5.40.66 | 105 | 4000 | 15020 | >80 | 220 - 240 / 50 - 60 | 7,0 | 66° |

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Beam Angle |
|--------------------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SFLS. 415.70.M1.40.66 | 70 | 4000 | 10100 | >80 | 220 - 240 / 50 - 60 | 6,7 | 66° |
| SFLS. 415.70.M2.40.66 | 70 | 4000 | 10100 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.70.M3.40.66 | 70 | 4000 | 10100 | >80 | 220 - 240 / 50 - 60 | 6,9 | 66° |
| SFLS. 415.70.M4.40.66 | 70 | 4000 | 10100 | >80 | 220 - 240 / 50 - 60 | 6,6 | 66° |
| SFLS. 415.70.M5.40.66 | 70 | 4000 | 10100 | >80 | 220 - 240 / 50 - 60 | 7,0 | 66° |

