



# S 0415 FLS



## Housing

Electrostatic powder coated aluminium injection and air pressure balancer (ventile) silicon gasket.

## Optics

Special design clear polycarbonate optic lens to transparent glass microprism deglaring lens option.

## Led

L85B50>50000 hours rated useful lifetime, high efficacy and color rendering index pf>0,95.

## Driver

Highly efficient with constant current output.

## Ambient Temperature

180W : -20 °C/+35 °C  
 150W : -20 °C/+40 °C  
 105W : -20 °C/+45 °C  
 70W : -20 °C/+60 °C

**Options** Dimming via DALI

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
SFLS. 415.180.M1.40.66	180	4000	23580	>80	220 - 240 / 50 - 60	6,7	66°
SFLS. 415.180.M2.40.66	180	4000	23580	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.180.M3.40.66	180	4000	23580	>80	220 - 240 / 50 - 60	6,9	66°
SFLS. 415.180.M4.40.66	180	4000	23580	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.180.M5.40.66	180	4000	23580	>80	220 - 240 / 50 - 60	7,0	66°
SFLS. 415.150.M1.40.66	150	4000	20400	>80	220 - 240 / 50 - 60	6,7	66°
SFLS. 415.150.M2.40.66	150	4000	20400	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.150.M3.40.66	150	4000	20400	>80	220 - 240 / 50 - 60	6,9	66°
SFLS. 415.150.M4.40.66	150	4000	20400	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.150.M5.40.66	150	4000	20400	>80	220 - 240 / 50 - 60	7,0	66°
SFLS. 415.105.M1.40.66	105	4000	15020	>80	220 - 240 / 50 - 60	6,7	66°
SFLS. 415.105.M2.40.66	105	4000	15020	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.105.M3.40.66	105	4000	15020	>80	220 - 240 / 50 - 60	6,9	66°
SFLS. 415.105.M4.40.66	105	4000	15020	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.105.M5.40.66	105	4000	15020	>80	220 - 240 / 50 - 60	7,0	66°

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
SFLS. 415.70.M1.40.66	70	4000	10100	>80	220 - 240 / 50 - 60	6,7	66°
SFLS. 415.70.M2.40.66	70	4000	10100	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.70.M3.40.66	70	4000	10100	>80	220 - 240 / 50 - 60	6,9	66°
SFLS. 415.70.M4.40.66	70	4000	10100	>80	220 - 240 / 50 - 60	6,6	66°
SFLS. 415.70.M5.40.66	70	4000	10100	>80	220 - 240 / 50 - 60	7,0	66°

