



# E 1506 UPM



## Housing

Produced through injection method, stroke and UV ray resistant Polycarbonate (PC).

## Optics

Produced through injection method, stroke-resistant, opal polycarbonate (PC) diffuser.

## Interior Housing

High quality steel sheet with electrostatic powder coating, mounted with special clips.

## Gasket

Ensoft S 160-26A- material monoblock gasket

## Led

High-efficacy LED MODULE with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and  $Pf \geq 0.95$ .

## Ambient Temperature

-20 °C/+40 °C (With Emergency Lighting Unit : 0 °C/+30 °C)

**Options** 1 or 3 hours emergency lighting kit  
Dimming via DALI

| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|
| EUPM.1506.45.30 | 45        | 3000    | 5830              | >80 | 220 - 240 / 50 - 60 | 2,5         |
| EUPM.1506.45.40 | 45        | 4000    | 6190              | >80 | 220 - 240 / 50 - 60 | 2,5         |

