



# E 1206 UPM



**Housing**

Produced through injection method, stroke and UV ray resistant Polycarbonate (PC).

**Optics**

Produced through injection method, stroke-resistant, opal polycarbonate (PC) diffuser.

**Interior Housing**

High quality steel sheet with electrostatic powder coating, mounted with special clips.

**Gasket**

Ensoft S 160-26A- material monoblock gasket

**Led**

High-efficacy LED MODULE with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

**Driver**

Constant current output LED driver with high efficiency and Pf≥0.95.

**Ambient Temperature**

-20 °C/+40 °C (With Emergency Lighting Unit : 0 °C/ +30 °C)

**Options** 1 or 3 hours emergency lighting kit  
Dimming via DALI

| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|
| EUPM.1206.36.30 | 36        | 3000    | 4640              | >80 | 220 - 240 / 50 - 60 | 2,0         |
| EUPM.1206.36.40 | 36        | 4000    | 4960              | >80 | 220 - 240 / 50 - 60 | 2,0         |

