



S 0500 HWK - Wide



Housing

Electrostatic powder coated aluminium injection and air pressure balancer (ventile).

Optics

Anodized aluminum reflector specially designed in three types as narrow, medium and wide angle.

Led

High-efficacy COB LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime.

Driver

Highly efficient with constant current output.

Glass

Clear tempered glass

Gasket

TPE (500600S)

Ambient Temperature

83W / 110W : -40 °C/+40 °C

137W : -40 °C/+30 °C

Options

Dimming via DALI

Mounting Accessory

Choose accessories according to the product mounting type.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) |
|-----------------------|-----------|---------|-------------------|-----|---------------------|-------------|
| SHWK.500.083.W. 40 | 83 | 4000 | 12060 | >80 | 220 - 240 / 50 - 60 | 7,3 |
| SHWK.500.110.W. 40 | 110 | 4000 | 16030 | >80 | 220 - 240 / 50 - 60 | 7,3 |
| SHWK.500.137.W. 40 | 137 | 4000 | 19720 | >80 | 220 - 240 / 50 - 60 | 7,3 |



