



CVU Series



Body

Matte natural anodized, aluminum extrusion profile and steel mounting accessory, aluminum end caps.

Diffuser

Opal white polycarbonate diffuser providing homogeneous light distribution.

LED

Mid power led with 50.000 hours lifetime, high efficacy factor and color rendering.

Driver

24V external type. High efficiency LED driver with constant current output system.



*Andz.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Cut-out Size (mm) |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|-------------------|
| SD0250CVU.05.30 | 5 | 3000 | 320 | >80 | 220 - 240 / 50 - 60 | 0,1 | 250 |
| SD0500CVU.10.30 | 10 | 3000 | 640 | 80 | 220 - 240 / 50 - 60 | 0,2 | 500 |
| SD1000CVU.20.30 | 20 | 3000 | 1250 | >80 | 220 - 240 / 50 - 60 | 0,4 | 1000 |
| SD1250CVU.25.30 | 25 | 3000 | 1250 | >80 | 220 - 240 / 50 - 60 | 0,5 | 1250 |
| SD1750CVU.35.30 | 35 | 3000 | 2250 | >80 | 220 - 240 / 50 - 60 | 0,7 | 1750 |
| SD2000CVU.42.30 | 42 | 3000 | 2550 | >80 | 220 - 240 / 50 - 60 | 0,8 | 2000 |



