

EDGE



A new range of recessed directional LED fixtures. Cooled with passive heatsink. The LED unit can be rotated horizontally with 355° and tilted vertically. Various shapes in single, double or triple configurations form a wide range of options in round, rectangular or dipped frames. Various accessories and colour combinations, including metallic gold, enable you to customize the experience and to create an atmosphere that underlines the exclusivity of the installation.

DESCRIPTION

A new range of recessed directional LED fixtures. Cooled with passive heatsink. The LED unit can be rotated 355° horizontally and tilted 25° vertically. Various shapes in single, double or triple configurations form a wide range of options in round, rectangular or dipped frames. Various accessories and colour combinations enable you to customize the experience and to create an atmosphere that underlines the exclusivity of the installation.

LED INFO

The Cree COB modules come in a variety of options of beam angle, output and colour temperature.

ORDERING

Light unit, frame, colours and accessories can be configured, allowing you to maximise flexibility. It is also possible to mix colours, beam angles and lumen intensities within one fixture.

RANGE

The range consists of a 70mm size LED module, later to be extended with a 50mm version. Available in various light outputs from 1200 to 3000lm with spot, medium and flood beams in 2700K, 3000K and 4000K. Standard available in CRI90. The LED driver is remote (to be placed on the ceiling) and available in fixed output or DALI control.

POWER SUPPLY

230-240V 50/60Hz (LED driver included) . DALI control available.

INSTALLATION

Installation in open or ventilated ceilings. Light unit snaps into pre-installed frame.

DATASHEET

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	lm/W
KOD EKLENECEK	10	950	2700	>90	220 - 240 / 50 - 60	95