S 0415 FEX Outdoor



Housing
Chromate coating, electrostatic powder coated aluminium inkection housing.

Optics
Special desing clear polycarbonate optic lens to transparent glass microprism deglaring lens and tempered clear glass.

LED
L90B50>50000 hours rated useful lifetime, highteffıcacy and color rendering index.

Driver
Highly efficent with constant current output.

Certificate
II 3G Ex nR IIC T6...T5 Gc
II 3D Ex tc IIIC T85°C...T 100°C Dc

Options
Dimming via DALI

Operating Temperature Range
-25°C/+40°C

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle	lm/W
FEX.OUT. 415.105.M1.40	105	4000	15630	80	220 - 240 / 50 - 60	9,1	66°	148
FEX.OUT. 415.150.M1.40	150	4000	21300	80	220 - 240 / 50 - 60	9,1	66°	142
FEX.OUT. 415.180.M1.40	180	4000	25240	80	220 - 240 / 50 - 60	9,1	66°	140
FEX.OUT. 415.105.M2.40	105	4000	15630	80	220 - 240 / 50 - 60	9,1	66°	148
FEX.OUT. 415.150.M2.40	150	4000	21300	80	220 - 240 / 50 - 60	9,1	66°	142
FEX.OUT. 415.180.M2.40	180	4000	25240	80	220 - 240 / 50 - 60	9,1	66°	140
FEX.OUT. 415.105.M3.40	105	4000	15630	80	220 - 240 / 50 - 60	9,1	66°	148
FEX.OUT. 415.150.M3.40	150	4000	21300	80	220 - 240 / 50 - 60	9,1	66°	142
FEX.OUT. 415.180.M3.40	180	4000	25240	80	220 - 240 / 50 - 60	9,1	66°	140

