



# Exproof Opus

## Housing

Matte natural anodized, aluminum extrusion profile and stainless-steel mounting accessories with polycarbonate end-cap.

## Optics

Opal, white, diffusing polycarbonate lens with lambertian light distribution.

## Led

High efficacy mid-power LED with CRI>80. Efficacy up to 145 lm/W L90B50 > 50,000 hours of life time.

## Driver

Constant current, have high efficiency and high power factor correction PF>0.9

## Gasket

Silicone

## Certificate

II 3G Ex nR IIC T6 Gc  
II 3D Ex tc IIIC T85°C Dc

## Ambient Temperature

-25 °C/+40 °C (With Emergency Lighting Unit : +5 °C/+30 °C)

## Options

1 or 3 hours emergency lighting kit  
Dimming via DALI

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	L (mm)	L1 (mm)
EXO.600.19.40	19	4000	2480	>80	220 - 240 / 50 - 60	1,9	635	652
EXO.600.26.40	26	4000	3440	>80	220 - 240 / 50 - 60	1,9	635	652
EXO.900.27.40	27	4000	3750	>80	220 - 240 / 50 - 60	2,6	923	940
EXO.900.38.40	38	4000	5045	>80	220 - 240 / 50 - 60	2,6	923	940
EXO.1200.34.40	34	4000	4680	>80	220 - 240 / 50 - 60	3,3	1211	1228
EXO.1200.49.40	49	4000	6300	>80	220 - 240 / 50 - 60	3,3	1211	1228
EXO.1500.44.40	44	4000	6420	>80	220 - 240 / 50 - 60	3,9	1500	1515
EXO.1500.61.40	61	4000	8530	>80	220 - 240 / 50 - 60	3,9	1500	1515

