



## 30° Optic Lens



### Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

### Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

### Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

### Driver

Constant current output LED driver with high efficiency and  $Pf \geq 95$ .

| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) | Beam Angle |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SUSKL.25W.30.30 | 25        | 3000    | 3890              | >80 | 220 - 240 / 50 - 60 | 2           | 30°        |
| SUSKL.25W.40.30 | 25        | 4000    | 4080              | >80 | 220 - 240 / 50 - 60 | 2           | 30°        |
| SUSKL.35W.30.30 | 35        | 3000    | 5470              | >80 | 220 - 240 / 50 - 60 | 2           | 30°        |
| SUSKL.35W.40.30 | 35        | 4000    | 5810              | >80 | 220 - 240 / 50 - 60 | 2           | 30°        |
| SUSKL.58W.30.30 | 58        | 3000    | 8790              | >80 | 220 - 240 / 50 - 60 | 2           | 30°        |
| SUSKL.58W.40.30 | 58        | 4000    | 9350              | >80 | 220 - 240 / 50 - 60 | 2           | 30°        |

