



# 100°/25° Optic Lens



## Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

## Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

## Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and Pf≥95.

| Type Code               | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) | Beam Angle |
|-------------------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SUSKL.25W.<br>30.100/25 | 25        | 3000    | 3990              | >80 | 220 - 240 / 50 - 60 | 2           | 100°/25°   |
| SUSKL.25W.<br>40.100/25 | 25        | 4000    | 4190              | >80 | 220 - 240 / 50 - 60 | 2           | 100°/25°   |
| SUSKL.35W.<br>30.100/25 | 35        | 3000    | 5580              | >80 | 220 - 240 / 50 - 60 | 2           | 100°/25°   |
| SUSKL.35W.<br>40.100/25 | 35        | 4000    | 5930              | >80 | 220 - 240 / 50 - 60 | 2           | 100°/25°   |
| SUSKL.58W.<br>30.100/25 | 58        | 3000    | 8890              | >80 | 220 - 240 / 50 - 60 | 2           | 100°/25°   |
| SUSKL.58W.<br>40.100/25 | 58        | 4000    | 9460              | >80 | 220 - 240 / 50 - 60 | 2           | 100°/25°   |



