



90°/50° Optic Lens



Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and Pf≥95.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
SUSKL.35W. 40.90/50	35	4000	5640	>80	220 - 240 / 50 - 60	2	90°/50°
SUSKL.35W. 30.90/50	35	3000	5400	>80	220 - 240 / 50 - 60	2	90°/50°
SUSKL.58W. 40.90/50	58	4000	9180	>80	220 - 240 / 50 - 60	2	90°/50°
SUSKL.58W. 30.90/50	58	3000	8640	>80	220 - 240 / 50 - 60	2	90°/50°
SUSKL.25W. 40.90/50	25	4000		>80	220 - 240 / 50 - 60	2	90°/50°
SUSKL.25W. 30.90/50	25	3000		>80	220 - 240 / 50 - 60	2	90°/50°



