



2x90°+3x100°/25° Optic Lens



Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and Pf≥95.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
SUSKL.25W.30.90+100/25	25	3000	3880	>80	220 - 240 / 50 - 60	2	2x90°+3x100°/25°
SUSKL.25W.40.90+100/25	25	4000	4070	>80	220 - 240 / 50 - 60	2	2x90°+3x100°/25°
SUSKL.35W.30.90+100/25	35	3000	5460	>80	220 - 240 / 50 - 60	2	2x90°+3x100°/25°
SUSKL.35W.40.90+100/25	35	4000	5730	>80	220 - 240 / 50 - 60	2	2x90°+3x100°/25°
SUSKL.58W.30.90+100/25	58	3000	8780	>80	220 - 240 / 50 - 60	2	2x90°+3x100°/25°
SUSKL.58W.40.90+100/25	58	4000	9200	>80	220 - 240 / 50 - 60	2	2x90°+3x100°/25°

