



## 60° Optic Lens



### Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

### Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

### Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

### Driver

Constant current output LED driver with high efficiency and  $Pf \geq 95$ .

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
SRSKR.25W.30.60	25	3000	3850	>80	220 - 240 / 50 - 60	3,5	60°
SRSKR.25W.40.60	25	4000	4050	>80	220 - 240 / 50 - 60	3,5	60°
SRSKR.35W.30.60	35	3000	5440	>80	220 - 240 / 50 - 60	3,5	60°
SRSKR.35W.40.60	35	4000	5790	>80	220 - 240 / 50 - 60	3,5	60°
SRSKR.58W.30.60	58	3000	8780	>80	220 - 240 / 50 - 60	3,5	60°
SRSKR.58W.40.60	58	4000	9330	>80	220 - 240 / 50 - 60	3,5	60°

Lamp: 1 x LED



