



# 90°/50° Optik Lens



## Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

## Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

## Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and Pf≥95.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
SRSKR.25W. 30.90/50	25	3000	3830	>80	220 - 240 / 50 - 60	3,5	90°/50°
SRSKR.25W. 40.90/50	25	4000	4020	>80	220 - 240 / 50 - 60	3,5	90°/50°
SRSKR.35W. 30.90/50	35	3000	5400	>80	220 - 240 / 50 - 60	3,5	90°/50°
SRSKR.35W. 40.90/50	35	4000	5640	>80	220 - 240 / 50 - 60	3,5	90°/50°
SRSKR.58W. 30.90/50	58	3000	8640	>80	220 - 240 / 50 - 60	3,5	90°/50°
SRSKR.58W. 40.90/50	58	4000	9180	>80	220 - 240 / 50 - 60	3,5	90°/50°

