



90°/50° Optik Lens



Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and Pf≥95.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Beam Angle |
|------------------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SRSKR.25W. 30.90/50 | 25 | 3000 | 3830 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90°/50° |
| SRSKR.25W. 40.90/50 | 25 | 4000 | 4020 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90°/50° |
| SRSKR.35W. 30.90/50 | 35 | 3000 | 5400 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90°/50° |
| SRSKR.35W. 40.90/50 | 35 | 4000 | 5640 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90°/50° |
| SRSKR.58W. 30.90/50 | 58 | 3000 | 8640 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90°/50° |
| SRSKR.58W. 40.90/50 | 58 | 4000 | 9180 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90°/50° |

