



# 130° Opal Diffuser



## Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

## Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

## Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

## Driver

Constant current output LED driver with high efficiency and  $Pf \geq 95$ .

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Weight (Kg)	Beam Angle
SOSKR.25W. 30.130	25	3000	3050	>80	220 - 240 / 50 - 60	3,2	130°
SOSKR.25W. 40.130	25	4000	3200	>80	220 - 240 / 50 - 60	3,2	130°
SOSKR.35W. 30.130	35	3000	4380	>80	220 - 240 / 50 - 60	3,2	130°
SOSKR.35W. 40.130	35	4000	4660	>80	220 - 240 / 50 - 60	3,2	130°
SOSKR.51W. 30.130	51	3000	6530	>80	220 - 240 / 50 - 60	3,2	130°
SOSKR.51W. 40.130	51	4000	6930	>80	220 - 240 / 50 - 60	3,5	130°



