# 25° Optic Lens



**Housing**
Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

**Optics**
Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

**Led**
High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

**Driver**
Constant current output LED driver with high efficiency and Pf≥95.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Beam Angle |
|---|---|---|---|---|---|---|---|
| SUSKR.25W.30.25 | 25 | 3000 | 3950 | >80 | 220 - 240 / 50 - 60 | 3,5 | 100°/25° |
| SUSKR.25W.40.25 | 25 | 4000 | 4150 | >80 | 220 - 240 / 50 - 60 | 3,5 | 100°/25° |
| SUSKR.35W.30.25 | 35 | 3000 | 5430 | >80 | 220 - 240 / 50 - 60 | 3,5 | 100°/25° |
| SUSKR.35W.40.25 | 35 | 4000 | 5700 | >80 | 220 - 240 / 50 - 60 | 3,5 | 25° |
| SUSKR.58W.30.25 | 58 | 3000 | 8780 | >80 | 220 - 240 / 50 - 60 | 3,5 | 25° |
| SUSKR.58W.40.25 | 58 | 4000 | 9220 | >80 | 220 - 240 / 50 - 60 | 3,5 | 25° |

