# 30° Optic Lens




**Housing**
Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.


**Optics**
Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.


**Led**
High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

**Driver**
Constant current output LED driver with high efficiency and Pf≥95.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Beam Angle |
|---|---|---|---|---|---|---|---|
| SUSKS.25W.30.30 | 25 | 3000 | 3890 | >80 | 220 - 240 / 50 - 60 | 3,5 | 30° |
| SUSKS.25W.40.30 | 25 | 4000 | 4080 | >80 | 220 - 240 / 50 - 60 | 3,5 | 30° |
| SUSKS.35W.30.30 | 35 | 3000 | 5470 | >80 | 220 - 240 / 50 - 60 | 2,5 | 30° |
| SUSKS.35W.40.30 | 35 | 4000 | 5810 | >80 | 220 - 240 / 50 - 60 | 3,5 | 30° |
| SUSKS.58W.30.30 | 58 | 3000 | 8790 | >80 | 220 - 240 / 50 - 60 | 3,5 | 30° |
| SUSKS.58W.40.30 | 58 | 4000 | 9350 | >80 | 220 - 240 / 50 - 60 | 3,5 | 30° |




1456
65
72
30


Max. 5m
72
1456
65