



90° Optic Lens



Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and Pf≥95.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Beam Angle |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SUSKS.25W.30.90 | 25 | 3000 | 3870 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90° |
| SUSKS.25W.40.90 | 25 | 4000 | 4060 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90° |
| SUSKS.35W.30.90 | 35 | 3000 | 5400 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90° |
| SUSKS.35W.40.90 | 35 | 4000 | 5730 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90° |
| SUSKS.58W.30.90 | 58 | 3000 | 8560 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90° |
| SUSKS.58W.40.90 | 58 | 4000 | 9050 | >80 | 220 - 240 / 50 - 60 | 3,5 | 90° |



